


TOILES TENDUES HAUTE TENSION



Dimensions:

PANELUXX R1


Diam. 18



ref: PAN1810

PANELUXX R2

Diam. 24



ref: PAN2415

Caractéristiques détaillées/ Detailed datas:

Modèle/ Model	PANELUXX R1	PANELUXX R2
Puissance/ Power	10 Watts	15 Watts
Source lumineuse/ Lighting source	CMS LED/ LED SMD	CMS LED/ LED SMD
Matière/ Material	Polycarbonate givré, aluminium anodisé/ Frosted polycarbonate, Anodised aluminium	Polycarbonate givré, aluminium anodisé/ Frosted polycarbonate, Anodised aluminium
Angle/ Beam Angle	120°	120°
Consommation/ Power consumption	12 Watts	18 Watts
Classe de protection/ Class of protection	II	II
Indice de protection/ IP	IP20	IP20
Durée de vie/ Life span	> 30 000 Heures/ > 30 000 Hours	> 30 000 Heures/ > 30 000 Hours
Alimentation/ Power supply	230V ac, alimentation incluse/ 230V ac, power supply included	230V ac, alimentation incluse/ 230V ac, power supply included
Flux lumineux/ Luminous flow	600 - 700 LM (Lumens)	850 - 1150 LM (Lumens)
Température de couleur/ Color temperature	Blanc chaud - Blanc neutre - Blanc froid/ Warm white - Neutral white - Cool white	Blanc chaud - Blanc neutre - Blanc froid/ Warm white - Neutral white - Cool white
Type d'installation/ Installation type	A encastrer	A encastrer